

FILTERS TELEPHONE LINE FILTERS



ETS-Lindgren's LTC Series Of Telephone Line Filters are ideal for applications including communication lines entering or leaving shielded rooms, computer rooms, communication terminal rooms, and Sensitive Compartmental Information Facilities (SCIF).

LTC-X640 filters have multiple circuits to handle 2, 4, 6, 8, 10 or 12 wires, and are designed for stand-alone, individual mounting. These filters may be supplied with an optional threaded conduit pipe for penetration of a shielded enclosure.

Standard Configuration

- These filters canisters can come without penetration.
- Wall mount

Options

- Penetration kit
- Order filters bundled with penetration kits for effortless shield installation.

TELEPHONE LINE FILTER SERIES

- For 2 to 12 Line LTC Filters
- Signal, Sensor & Voice Communication
- Data Communication
- Control Line

Technical Specifications

Electrical (Max. Rating)

Model	Current Rating	Voltage Rating
LTC-2640-C10K	2 x 0.5 A	0 - 125 VAC
LTC-4640-C10K	4 x 0.5 A	0 - 125 VAC
LTC-6640-C10K	6 x 0.5 A	0 - 125 VAC
LTC-8640-C10K	8 x 0.5 A	0 - 125 VAC
LTC-10640-C10K	10 x 0.5 A	0 - 125 VAC
LTC-12640-C10K	12 x 0.5 A	0 - 125 VAC
LTC-2640-D56K	2 x 0.5 A	0 - 125 VAC
LTC-4640-D56K	4 x 0.5 A	0 - 125 VAC
LTC-6640-D56K	6 x 0.5 A	0 - 125 VAC
LTC-8640-D56K	8 x 0.5 A	0 - 125 VAC
LTC-10640-D56K	10 x 0.5 A	0 - 125 VAC
LTC-12640-D56K	12 x 0.5 A	0 - 125 VAC
LTC-2640-E128K	2 x 0.5 A	0 - 125 VAC
LTC-4640-E128K	4 x 0.5 A	0 - 125 VAC
LTC-6640-E128K	6 x 0.5 A	0 - 125 VAC
LTC-8640-E128K	8 x 0.5 A	0 - 125 VAC
LTC-10640-E128K	10 x 0.5 A	0 - 125 VAC
LTC-12640-E128K	12 x 0.5 A	0 - 125 VAC
LTC-12640-E128K	12 x 640 A	0 - 125 VAC

FILTERS TELEPHONE LINE FILTERS

Physical Specifications				
Model	Case Length "A"	Case Width "B"	Case Height "C"	Approx. Weight
LTC-2640-C10K	38.3 cm (15.25 in)	7.62 cm (3.00 in)	5.1 cm (2 in)	5 lbs
LTC-4640-C10K	38.3 cm (15.25 in)	5.24 cm (6.00 in)	5.1 cm (2 in)	10 lbs
LTC-6640-C10K	38.3 cm (15.25 in)	30.48 cm (12.00 in)	5.1 cm (2 in)	15 lbs
LTC-8640-C10K	38.3 cm (15.25 in)	30.48 cm (12.00 in)	5.1 cm (2 in)	20 lbs
LTC-10640-C10K	38.3 cm (15.25 in)	45.72 cm (18.00 in)	5.1 cm (2 in)	25 lbs
LTC-12640-C10K	38.3 cm (15.25 in)	45.72 cm (18.00 in)	5.1 cm (2 in)	30 lbs
LTC-2640-D56K	38.3 cm (15.25 in)	7.62 cm (3.00 in)	5.1 cm (2 in)	5 lbs
LTC-4640-D56K	38.3 cm (15.25 in)	5.24 cm (6.00 in)	5.1 cm (2 in)	10 lbs
LTC-6640-D56K	38.3 cm (15.25 in)	30.48 cm (12.00 in)	5.1 cm (2 in)	15 lbs
LTC-8640-D56K	38.3 cm (15.25 in)	30.48 cm (12.00 in)	5.1 cm (2 in)	20 lbs
LTC-10640-D56K	38.3 cm (15.25 in)	45.72 cm (18.00 in)	5.1 cm (2 in)	25 lbs
LTC-12640-D56K	38.3 cm (15.25 in)	45.72 cm (18.00 in)	5.1 cm (2 in)	30 lbs
LTC-2640-E128K	38.3 cm (15.25 in)	7.62 cm (3.00 in)	5.1 cm (2 in)	5 lbs
LTC-4640-E128K	38.3 cm (15.25 in)	15.24 cm (6.00 in)	5.1 cm (2 in)	10 lbs
LTC-6640-E128K	38.3 cm (15.25 in)	30.48 cm (12.00 in)	5.1 cm (2 in)	15 lbs
LTC-8640-E128K	38.3 cm (15.25 in)	30.48 cm (12.00 in)	5.1 cm (2 in)	20 lbs
LTC-10640-E128K	38.3 cm (15.25 in)	45.72 cm (18.00 in)	5.1 cm (2 in)	25 lbs
LTC-12640-E128K	38.3 cm (15.25 in)	45.72 cm (18.00 in)	5.1 cm (2 in)	30 lbs

