

PROBE INTERFACE HI-4413USB FIBER TO USB CONVERTER



ETS-Lindgren's HI-4413USB Fiber to USB Converter is an economical way to collect and display data from all of the ETS-Lindgren battery powered EMC optically coupled field probes. Connecting to the USB port of a personal computer, the HI-4413USB provides the interface with power directly from the USB port, so no external power supply is required.

ProbeView LT software (available for download from our website) provides a simple tool for collecting data and storing the field values on a personal computer. ProbeView II is available at additional cost and provides real-time display, logging and analysis functions of EMF data. It can display a variety of test information, both numerically and graphically. A field intensity versus time graph is on the main screen along with the maximum field, X, Y, Z, and RMS values in addition to a variety of data logging options.

HI-4413USB FIBER TO USB CONVERTER

- Fiber Optic Modem
- Connects to a PC USB Port
- Operational With ETS-Lindgren Battery Powered field Probes
- No External Power Supply
- ProbeView LT Available for Download
- Fully Compatible with ProbeView II Software (Sold Separately)

Technical Specifications

Electrical

Optical Connectors	FSMA (2)
USB Connector	USB Mini B

Physical

Length	4.8 cm (1.89 in)
Width	3.18 cm (1.25 in)
Thickness	1.91 cm (0.75 in)